

VERTIMAX MANURE SPREADER



- Available: 16' to 18' long Single Axle & 20' to 22' long Tandem Axle
- 6'6" inside
- Guillotine gate
- Heavy Duty WR78 Floor Chain
- 650 / 55R26.5 Alliance tires
- Over running clutch
- Shear bolt protection



VERTIMAX MANURE SPREADER

SPECIFICATION DETAILS:



	VM1603	VM1803
Axle	Single	Single
Axle beam size	4"	5"
Carrying capacity	23,000 lbs	29,500 lbs
Level capacity	315 ft ³	354 ft ³
Heaped capacity	420 ft ³	472 ft ³
Body size	16'x6'6"x3'	18'x6'6"x3'
Floor drive	Hydraulic	Hydraulic
Floor chain style	WR78	WR78
Tire size	650/55R26.5	650/55R26.5
Spread mech	Twin vertical augers	Twin vertical augers
Spread width	up to 55'	up to 55'
PTO speed	1000 RPM	1000 RPM
Floor material	1/2" HMW	1/2" HMW
Wall material	10 gauge	10 gauge
Empty weight	9,000 lbs	10,500 lbs

STANDARD SPECIFICATION:

- Dynamically balanced twin vertical augers
- Hydraulic guillotine gate
- New robust one piece gearbox
- Auger gearbox protection via shearbolt
- Thicker high tensile 3/8" auger flights
- Reversible cutters
- Floor protected by cross line relief valve
- Low friction, 1/2" HMW floor
- Long lasting composite floor shaft bearings
- Heavy Duty WR78 Floor Chain
- Large diameter wheels for low ground pressure characteristics

- Fully welded heavy duty construction
- Heavy duty fold away lights
- 2' mesh bulk head
- Handles all manure types and other materials
- Epoxy primer & two part urethane paint
- 12,000 # spring loaded jack
- CV head on tractor PTO shaft
- Spinner cowl

OPTIONAL EQUIPMENT:

- Extension sides 12"
- Extension sides flared
- Non standard finish colours
- Wheel options

This machine is designed for off-road Agricultural use only. For other applications, please contact J. Bond & Sons Ltd. J. Bond & Sons Ltd. reserves the right to improve or modify our product without notice or obligation.



AUTHORIZED DEALER

Unit D, 7116 Beatty Drive, Mission, BC V2V 6B4
 Phone: 604-826-5391 • Cell: 604-835-1733 • Fax: 604-826-5392
 E-mail: sales@jbscanada.ca • www.jbscanada.ca