

JBS SAND SLINGER



- Available: 10' to 16' long, 4' or 5' walls, truck mount or pull type
- Hydraulic front door to meter sand flow
- High torque motor & gearbox for increased power & reliability
- Discharges both directions
- Adjustable conveyor angle



JBS SAND SLINGER



STANDARD SPECIFICATION:

- All components hydraulically driven
- Can bed up to 12' - 15'
- Can be used with sand and a variety of bedding materials
- Standard heavy duty WR78 big barrel chain
- Jack 12,000# spring loaded
- Hydraulic flow control for apron chain speed adjustments

SPECIFICATION DETAILS:

| | SS1048 | SS1248 | SS1460 | SS1660 |
|-----------------------------|---------------------|-----------------------|-----------------------|-----------------------|
| Axle | Single | Single | Tandem | Tandem |
| Capacity (with sand) | 18,920 | 22,704 | 35,112 | 40,128 |
| Volume | 172 ft ³ | 206.4 ft ³ | 319.2 ft ³ | 364.8 ft ³ |
| Body size (LxWxH) | 10' x 4' x 4' | 12' x 4' x 4' | 14' x 4' x 5' | 16' x 4' x 5' |
| Top opening width | 66" | 66" | 73" | 73" |
| Floor chain | WR78 | WR78 | WR78 | WR78 |
| Tires | Used 385/65R22.5 | Used 385/65R22.5 | Used 385/65R22.5 | Used 385/65R22.5 |
| Hub/Spindle cap | 20,000 lb | 20,000 lb | 40,000 lb | 40,000 lb |

*This machine is designed for off-road Agricultural use only. For other applications, please contact J. Bond & Sons Ltd.
J. Bond & Sons Ltd. reserves the right to improve or modify our product without notice or obligation.*



Unit D, 7116 Beatty Drive, Mission, BC V2V 6B4
 Phone: 604-826-5391 • Cell: 604-835-1733 • Fax: 604-826-5392
 E-mail: sales@jbscanada.ca • www.jbscanada.ca

AUTHORIZED DEALER