

VERTIMAX TRUCK MOUNTED MANURE SPREADER



- Available from 16' to 26' long
- 6'6" inside
- Guillotine gate
- Heavy Duty WR78 Floor Chain
- Over running clutch
- Shear bolt protection



VERTIMAX TRUCK MOUNTED MANURE SPREADER

SPECIFICATION DETAILS:



| | VMT1836 | VMT2036 |
|-------------------------|----------------------|----------------------|
| Level capacity | 354 ft ³ | 390 ft ³ |
| Heaped capacity | 472 ft ³ | 520 ft ³ |
| Body size | 18'x6'6"x3' | 20'x6'6"x3' |
| Floor drive | Hydraulic | Hydraulic |
| Spreader drive | Hydraulic | Hydraulic |
| Floor chain style | WR78 | WR78 |
| Spread mech | Twin vertical augers | Twin vertical augers |
| Spread width | up to 55' | up to 55' |
| Floor material | 1/2" HMW | 1/2" HMW |
| Wall material | 10 gauge | 10 gauge |
| Box & attachment weight | 9,000 lbs | 10,000 lbs |

STANDARD SPECIFICATION:

- Dynamically balanced twin vertical augers
- Hydraulic guillotine gate
- New robust one piece gearbox
- Auger gearbox protection via shearbolt
- Thicker high tensile 3/8" auger flights
- Reversible cutters
- Floor protected by cross line relief valve
- Low friction, 1/2" HMW floor
- Long lasting composite floor shaft bearings
- Heavy duty WR78 floor chain

- Fully welded heavy duty construction
- 2' mesh bulk head
- Handles all manure types and other materials
- Epoxy primer & two part urethane paint
- Spinner cowling

OPTIONAL EQUIPMENT:

- Beater upgrade to 5/8" auger flighting
- Wall heights
- Electric/hydraulic controls
- Angled or straight bulkhead
- Fenders with mud flaps
- Extension sides 12"
- Extension sides flared
- Non standard finish colours

This machine is designed for off-road Agricultural use only. For other applications, please contact J. Bond & Sons Ltd. J. Bond & Sons Ltd. reserves the right to improve or modify our product without notice or obligation.



AUTHORIZED DEALER

Unit D, 7116 Beatty Drive, Mission, BC V2V 6B4
 Phone: 604-826-5391 • Cell: 604-835-1733 • Fax: 604-826-5392
 E-mail: sales@jbscanada.ca • www.jbscanada.ca