

VERTIMAX TANDEM MANURE SPREADER

**VERTI-
MAX**



- Available 20', 22' or 24' long with a 3' or 4' high wall.
- 6'6" Inside
- Guillotine gate
- Heavy duty WR78 floor chain
- 550/45 22.5 tires standard
- 620/40 22.5 tires optional
- Over running clutch
- Shear bolt protection



VERTIMAX TANDEM MANURE SPREADER

SPECIFICATION DETAILS:

	VM2048	VM2248	VM2448
Axle	Tandem	Tandem	Tandem
Axle beam size	130mm (5 1/8")	130mm (5 1/8")	130mm (5 1/8")
Carrying capacity	65,000 lbs	65,000 lbs	65,000 lbs
Level capacity	520 ft ³	572 ft ³	624 ft ³
Heaped capacity	650 ft ³	715 ft ³	780 ft ³
Body size	20'x6'6"x4'	22'x6'6"x4'	24'x6'6"x4'
Floor drive	Hydraulic	Hydraulic	Dual Hydraulic
Floor chain style	WR78	WR78	WR78
Tire size	550/45 22.5	550/45 22.5	620/40 22.5
Spread mech	Twin vertical augers	Twin vertical augers	Twin vertical augers
Spread width	up to 55'	up to 55'	up to 55'
PTO speed	1000 RPM	1000 RPM	1000 RPM
Floor material	1/2" UHMW	1/2" UHMW	1/2" UHMW
Wall material	10 gauge	10 gauge	10 gauge
Empty weight	15,500 lbs	16,500 lbs	17,500 lbs



Heavy Duty WR78 Floor Chain

STANDARD SPECIFICATION:

- Dynamically balanced twin vertical augers
- Hydraulic guillotine gate
- New robust one piece gearbox
- Auger gearbox protection via shearbolt
- Thicker high tensile 3/8" auger flights
- Reversible cutters
- Floor protected by cross line relief valve
- Low friction, 1/2" UHMW floor
- Long lasting composite floor shaft bearings
- Heavy duty WR78 floor chain
- Tandem axle suspension for low ground pressure characteristics

- High capacity spring suspension walking beam hyd. brakes and rear steering. Completely greasable and very low maintenance.
- Fully welded heavy duty construction
- Heavy duty fold away lights
- 2' mesh bulk head
- Handles all manure types and other materials
- Epoxy primer & two part urethane paint
- 12,000 # spring loaded jack
- Size 8 CV head on tractor PTO Shaft
- Spinner cowl

OPTIONAL EQUIPMENT:

- Non standard finish colours
- 2 tire options
- 5/8" auger flighting
- Single or dual floor drives

This machine is designed for off-road Agricultural use only. For other applications, please contact J. Bond & Sons Ltd. J. Bond & Sons Ltd. reserves the right to improve or modify our product without notice or obligation.

JBS Ltd.

Unit D, 7116 Beatty Drive, Mission, BC V2V 6B4

Phone: 604-826-5391 · Cell: 604-835-1733 · Fax: 604-826-5392

E-mail: sales@jbscanada.ca · www.jbscanada.ca

AUTHORIZED DEALER