

## VERTIMAX TANDEM WIDE BODY MANURE SPREADER

**WIDE  
BODY**



**VERTI-  
MAX**

- Available 20', 22' or 24' long with a 4' high wall.
- 7'4" Inside
- Guillotine gate
- Heavy duty WR78 floor chain
- 550/45 22.5 tires standard
- 620/40 22.5 tires optional
- 700/45R 22.5 tires optional
- Over running clutch
- Shear bolt protection



# VERTIMAX TANDEM WIDE BODY MANURE SPREADER

## SPECIFICATION DETAILS:



	VMWB2048	VMWB2248	VMWB2448
<b>Axle</b>	Tandem	Tandem	Tandem
<b>Axle beam size</b>	130mm (5 1/8")	130mm (5 1/8")	130mm (5 1/8")
<b>Carrying capacity</b>	65,000 lbs	65,000 lbs	65,000 lbs
<b>Level capacity</b>	592 ft <sup>3</sup>	651 ft <sup>3</sup>	710 ft <sup>3</sup>
<b>Heaped capacity</b>	740 ft <sup>3</sup>	814 ft <sup>3</sup>	888 ft <sup>3</sup>
<b>Body size</b>	20'x7'4"x4'	22'x7'4"x4'	24'x7'4"x4'
<b>Floor drive</b>	Dual Hydraulic	Dual Hydraulic	Dual Hydraulic
<b>Floor chain style</b>	WR78	WR78	WR78
<b>Tire size</b>	550/45 22.5	550/45 22.5	620/40R 22.5
<b>Spread mech</b>	Twin vertical augers	Twin vertical augers	Twin vertical augers
<b>Spread width</b>	up to 55'	up to 55'	up to 55'
<b>PTO speed</b>	1000 RPM	1000 RPM	1000 RPM
<b>Floor material</b>	1/2" HMW	1/2" HMW	1/2" HMW
<b>Wall material</b>	10 gauge	10 gauge	10 gauge
<b>Empty weight</b>	20,500 lbs	22,500 lbs	24,500 lbs

### STANDARD SPECIFICATION:

- Dynamically balanced twin vertical augers
- Hydraulic guillotine gate
- Auger gearbox protection via shearbolt
- Thicker high tensile 5/8" auger flights
- Reversible cutters
- Low friction, 1/2" UHMW floor
- Long lasting composite floor shaft bearings
- Heavy duty WR78 floor chain with tubing cross slats
- 26 ton Tandem axle suspension for low ground pressure characteristics
- High capacity spring suspension walking beam hyd. brakes and rear steering. Completely greasable and very low maintenance.
- Fully welded heavy duty construction
- Heavy duty fold away lights
- 2' mesh bulk head
- Handles all manure types and other materials

*This machine is designed for off-road Agricultural use only. For other applications, please contact J. Bond & Sons Ltd.  
J. Bond & Sons Ltd. reserves the right to improve or modify our product without notice or obligation.*

- Epoxy primer & two part urethane paint
- 12,000 # spring loaded jack
- Size 8 CV head on tractor PTO Shaft
- Spinner cowling
- Steel idler sprocket with Bronze Bushings
- Swivel hitch
- Largest Vertical Beater Gearbox in the industry (30% larger then standard Vertimax)
- Enclosed large bearings on top of Beaters

### OPTIONAL EQUIPMENT:

- Non standard finish colours
- 2 tire options
- Wall extension
- Pen Pack flip up door in tailgate for larger opening

# JBS Ltd.

AUTHORIZED DEALER

Unit D, 7116 Beatty Drive, Mission, BC V2V 6B4  
 Phone: 604-826-5391 · Cell: 604-835-1733 · Fax: 604-826-5392  
 E-mail: sales@jbscanada.ca · www.jbscanada.ca