

VERTIMAX TRIDEM MANURE SPREADER



- Large 30' long box
- 6'6" inside
- Guillotine gate
- Heavy duty WR78 floor chain
- 620/40 22.5 tires
- Over running clutch
- Shear bolt protection



VERTIMAX TRIDEM MANURE SPREADER



SPECIFICATION DETAILS:

	VM3048
Axle	Tridem
Axle beam size	127mm (5")
Carrying capacity	85,000 lbs
Level capacity	780 ft ³
Heaped capacity	975 ft ³
Body size	30'x6'6"x4'
Floor drive	Dual Hydraulic
Floor chain style	WR78
Tire size	620/40 22.5
Spread mech	Twin Vertical Augers
Spread width	up to 55'
PTO speed	1000 RPM
Floor material	1/2" HMW
Wall material	10 gauge
Empty weight	25,000 lbs

STANDARD SPECIFICATIONS:

- Dynamically balanced twin vertical augers
- Hydraulic guillotine gate
- New robust one piece gearbox
- Auger gearbox protection via shearbolt
- Thicker high tensile 5/8" auger flights
- Reversible cutters
- Low friction, 1/2" UHMW floor
- Long lasting composite floor shaft bearings
- Heavy duty WR78 floor chain
- Tridem axle suspension for low ground pressure characteristics

- High capacity spring suspension. Completely greasable with oil bath hubs and very low maintenance.
- Fully welded heavy duty construction
- Heavy duty fold away lights
- 2' mesh bulk head
- Handles all manure types and other materials
- Epoxy primer & two part urethane paint
- 12,000 # spring loaded jack
- Size 8 CV head on tractor PTO Shaft
- Spinner cowl

OPTIONAL EQUIPMENT:

- Non standard finish colours
- 2 tire options
- Wall extensions

This machine is designed for off-road Agricultural use only. For other applications, please contact J. Bond & Sons Ltd. J. Bond & Sons Ltd. reserves the right to improve or modify our product without notice or obligation.

JBS Ltd.

Unit D, 7116 Beatty Drive, Mission, BC V2V 6B4

Phone: 604-826-5391 · Cell: 604-835-1733 · Fax: 604-826-5392

E-mail: sales@jbscanada.ca · www.jbscanada.ca

AUTHORIZED DEALER